

Flask heaters

KI



Single and serial flask heaters. The energy controller is fully adjustable. Heaters are equipped with excess current switch and pilot lamp.

Application

Thanks to the broad variety of accessories the hotplates can be used as:

- Extraction units
- Crude fiber units
- Hydrolysis units
- Digestion units
- Distillation units

Available models

Single heater

- KI1 Single heater, 1 place, 600 °C, 230 V 50-60 Hz 450 W for flasks 50 ml to 250 ml, order no. 10-0003
- KI2 Single heater, 1 place, 650 °C, 230 V 50-60 Hz 580 W for flasks 250 ml to 1000 ml, order no. 10-0004

Serial heaters

- KI16 Serial heater, 6 places, 600 °C, 230 V 50-60 Hz 1800 W for flasks 50 ml to 250 ml, order no. 10-0007
- KI24 Serial heater, 4 places, 650 °C, 230 V 50-60 Hz 2320 W for flasks 250 ml to 750 ml, order no. 10-0008
- KI26 Serial heater, 6 places, 650 °C, 400 V 3P+N, 50-60 Hz 3480 W for flasks 250 ml to 750 ml, order no. 10-0009

Accessories for the heating of flasks

- Support rod 600 mm, order no. 10-0097
- Support rod 1000 mm, order no. 10-0100
- Forked rod with screw thread, order no. 10-0098

