

HYDROXYPROLINE DIGESTION UNIT

Digestion unit specifically designed for the determination of hydroxyproline content.

Proven C. Gerhardt technology based on the KJELDATHERM heating block with precision temperature control.

Test tubes with screw caps, acid-resistant varnish on the sheet metal components.

The working temperature cannot exceed 240 °C

Scope of delivery KJELDATHERM-digestion block

Multi-level console

Insert rack for digestion tubes

Digestion tubes with screw caps GL45

Electronic temperature controller



HYDROXYPROLIN Digestion unit

Type	HXP20
TECHNICAL DATA	
Heating places	20
Volume of tubes [ml]	250
Temperature max. [°C]	240
Nominal wattage [W]	1000
Dimensions W / D / H [mm]	515 / 483 / 728
Weight [kg]	ca. 37
Nominal voltage [VAC]	230
Frequency [Hz]	50 - 60
DELIVERY	
KJELDATHERM-digestion block	1 x
Insert rack 20-place	1 x
Multi level console	1 x
Digestion tube Hydroxyprolin	20 x
Temperature-Controller	1 x
ORDER INFORMATION	
Version 230 V	12-0795

Accessories

Order No.	Description
12-0316	Digestion tube for hydroxyproline determination, 250ml, with GL45 cap + seal
1002270	Screw cap GL 45 closed version with seal for 12-0316
12-0723	Insert rack EB20, white, for 20 x 250 ml digestion tubes

More accessories and consumables on request.

